

DATA LOGGERS

8 CHANNELS MODEL PRTL DL 9060
16 CHANNELS MODEL PRTL DL 9061

Features

- Panel mountable.
- Upto 16 channels.
- Auto / man mode selectable.
- μ P based.
- Variable scan rate, print time.
- In built real time.
- Centronics parallel printer port.

APPLICATIONS

- Furnace Industries.
- Ovens and incubators.
- Laboratory equipments.
- Environmental chambers.
- Pharmaceutical industry.
- No of channels limit facility.
- Two relay alarm outputs.
- 60 VAC to 265 VAC power supply.
- All types of TCS, RTDs, 0 to 5V or 4-20 mA I/Ps.
- Display of channel number, pv and real time.
- ± 1 or 0.1 count resolution or accuracy.
- 7 segment LED display.
- Touch key interface.
- Blood bank refrigerators.
- Quality control and maintenance.
- Medical equipments.
- Heat treatment.
- Any process control application.



SPECIFICATIONS

POWER SUPPLY : 60VAC to 265 VAC.

OUTPUTS : Dual relay alarm O/Ps.

DISPLAY : 7 segment 1/2" or 1/4" LED displays for Ch no, PV and real time.

RELAY STATUS : Through LEDs.

INTERFACE : Centronics parallel printer interface.

NO. OF CHANNELS : 8 channels or 16 channels.

OUTPUT RATING : Upto 1A max resistive.

RESOLUTION : 0.1 or 1 count.

ACCURACY : ± 0.1 or 1 count.

USER INTERFACE: Through front panel touch keys.

MODES : Auto / man mode selectable.

SETTABLE PARAMETERS : Scan rate, Print rate, Alarm, and real time setting etc.,

DIMENSION : 96x96x135mm.

MOUNTING : Panel mountable.

ENCLOSURE : ABS plastic.



PROTROL

Process Control People

15, 5th Cross, Varma Layout, Bhuvaneshwari Nagar, H.A. Farm Post, Bangalore - 560 024.

Phone : 080 23338824, Fax : 080 23437068, Mobile : 98451 62279, E-mail : protrol@vsnl.com, Internet : www.protrol.com